JTouch



Large touchscreen displays to engage your audience and fit your budget

Part# INFA2155/INFA2165/INFA2170/INFA2184/INFA2198

The InFocus JTouch combines precise touchscreen technology with a bright, colourful LCD display to engage audiences in classrooms and beyond

- 55", 65", 70", 84", 98", 1080P to 4K*2K touch display for a great price
- Add touch to your system's Windows apps, even the older ones
- Your content will be interactive, bright and crisp in any light
- Accurate and responsive touch overlay with multi-touch capability
- Quickly connect and display your PC and notebook via HDMI, VGA and more
- Convenient interfaces on the front and back for easy and quick connect to external devices



JTouch helps you get your message across and connect with your audience with incredible brightness, colour and clarity. Your images, text and video will be seen and enjoyed even in large spaces with high ambient light.

Engage Your Audience with Touch

Whether you're in a classroom, board room or at a trade show, the interactivity of JTouch engages audience and encourages participation. JTouch gets students involved, attracts customers, and provides a great medium for testing and presenting touch-enabled applications.

Easy to Connect

JTouch provides multiple ways to display your content, including HDMI, VGA, and wireless via optional InFocus LiteShow adapter. To enable touch, simply connect the JTouch to your computer via USB.





Multi-touch with Gestures

Use multi-point touch gestures to manipulate your content and traverse your Windows, Mac or Chrome device on the giant touchscreen. Your software and content will come to life on a giant scale to engage your audience and encourage their interaction.

Location, Location, Location

Secure the JTouch to the wall with its standard VESA mounting pattern or mount it on an optional InFocus mobile cart. A mobile cart lets you position it in multiple locations within a room or share it between multiple rooms – whenever it's needed most.



Specifications*

Display	INFA2155	INFA2165	INFA2170		INFA2184	INFA2198			
Size	55"	65"	70"		84"	98"			
Resolution	1920 x 1080			3840 x 2160					
Scan speed	60 Hz			30 Hz					
Viewing Angle	178°(H) / 178°(V)								
Technology	LED backlight LCD								
Pixel Pitch	0.63 mm	0.744 mm	0.807mm	1	0.4845mm	0.5622mm			
Response Time		8 ms 5 ms							
Contrast Ratio	300	0:1	4000:1		3000:1				
Brightness	650 nits	650 nits	700 nits		650 nits	750 nits			
Computer Compatibility	Display: PC/Mac/Chromebook Multi-Touch: Windows 7/8, Android, Single-Touch: Win7/8/XP/Vista/Linux/Mac/Android/Wince								
Connections	HDMI*4,VGA*1,PC- Audio*1,YPBPR*1,AV- Input*1,AV- Output*1,USB(PC)*2,US B(Touch)*2,TV-Audio output*1,TV-Mic input*1,RS232- In*1,RS232-Out*1	HDMI*6,VGA*1, PC- Audio*1,YPBPR*1,YPBPR -Audio*1,LAN*1,TV input*1,AV-Input*1,AV- Output*1,3.5 mini jack*1,Coaxial*1,USB(TV)*2,USB(PC)*1,USB(Touc h)*1,TV-Audio output*1,TV-Mic input*1,RS232- In*1,RS232-Out*1	HDMI*6,VGA*1, Audio*1,YPBPR*1,Y -Audio*1,LAN*1, input*1,AV-Input*1 Output*1,3.5 m jack*1,Coaxial*1,US h)*1,TV-Audio output*1,TV-M input*1,RS232	YPBPR .,TV f1,AV- nini ISB(TV B(Touc o Mic	HDMI- UD*1,HDMI*4,VGA*1,P C- Audio*1,YPBPR*1,YPBPR -Audio*1,LAN*1,TV Input*1,AV Input*1,AV Output*1,3.5 mini jack*1,Coaxial*1,CVBS Audio*1,USB(TV)*1,USB(PC)*1,USB(Touch)*1,TV- Mic Input*1,RS232- In*1,RS232-Out*1	HDMI- UD*1,HDMI*4,VGA*1,P C- Audio*1,YPBPR*1,YPBPR -Audio*1,LAN*1,TV Input*1,AV Input*1,AV Output*1,3.5 mini jack*1,Coaxial*1,USB(TV)*1,USB(PC)*1,USB(Touc h)*1,TV-Mic Input*1,RS232- In*1,RS232-Out*1			
Touch Screen	High precise infrared touch frame with 4mm tempered glass								
Touch Points	6 points								
Speakers (Integrated)	10W*2								
Power	100 – 240V, 50 – 60Hz								
Mount	VESA 4-M6 400 x 405mm	VESA	VESA 6-M8 800mm x (400+300)mm						

System

Accessories	Remote control, Power cord, Touch USB cable, Touch pen							
Warranty	1 year warranty							
Product Weight	40.7kg±1.5kg	60.6kg±1.5kg	72kg±1.5kg	142kg±1.5kg	162kg±1.5kg			
Product Dimensions	1290x100x782.64	1536x82x931	1636.9x96.3x981.45	1965.2x87.6x1164.2	2245.4x91.7x1321.8			
Shipping Weight	47.55kg±1.5kg	82.8kg±1.5kg	93.5kg±1.5kg	173kg±1.5kg	214kg±1.5kg			
Shipping Dimensions	1520x245x965	1765x320x1165	1895x340x1210	2230x405x1490	2525x435x1870			
Operating Conditions	0°C - 50 °C		0°C - 40 °C					

Accessories

LiteShow Wireless Adapter (INLITESHOW4)
BigNote Whiteboard Software (INS-BIGNOTE)
MondoCenter Collaboration PC (INF-MCENTER2)
USB to HDMI Adapter (HW-USB2HDMI)



^{*}Product specifications, terms, and offerings are subject to change at any time without notice.